

Model	Jazzy® EVO 614 ¹
Weight Capacity	300 lb / 136 kg
Turning Radius ³	22"
Overall Width ³	25.4"
Overall Length ³	40"
Maximum Speed ²	Up to 4.4 mph / 7 km/h
Ground Clearance ³	3"
Front Casters ³	6"
Drive Wheels ³	13.75" perforated
Rear Casters ³	6"
Drivetrain	Two in-line HD motors
Braking System	Regenerative and electromechanical
Suspension Type	Full independent front and rear Active-Trac® ATX Suspension
High-back Seat Sizes ³	16"x16"-18" 18"x18"-20" 20"x18"-20"
Seat-to-Floor Range ³	22"-24"
Per Charge Range ^{2,5}	Up to 19 mi / 30.6 km at 300 lb / 136 kg Up to 21.5 mi / 34.6 km at 200 lb / 90.7 kg
Standard Electronics	60A Dynamic Linx
Component Weights ⁶	Base: 125.7 lb / 57 kg Seat: 57.8 lb / 26.2 kg Batteries: (2) 36 lb / 16.3 kg each
Total Weight ⁴	255.5 lb / 115.9 kg
Battery Requirements	(2) NF-22
Battery Charger	5 amp, off-board
Warranty	Frame: 5-year limited Drivetrain: 24-month limited Electronics: 24-month limited Battery: 13-month limited

¹ Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.

² Varies with user weight, terrain, battery type, battery condition and tire pressure. This specification can be subject to a variance of +10%, -5%.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

⁴ Total weight includes base, seat and batteries.

⁵ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities.

⁶ Battery weight may vary based on manufacturer.

PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

pridemobility.ca | yfti

The information contained herein is correct at time of publication; we reserve the right to alter specifications without prior notice.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.

CA0004778-030323



Jazzy[®]
EVO 614

THIS IS JAZZY
EVOLVED



FDA Class II
Medical Device¹

CANADA'S FAVORITE POWER CHAIR
pridemobility.ca

THIS IS JAZZY EVOLVED

Built for Indoor and Outdoor Adventures

The Jazzy EVO 614 is your ultimate mobility alternative. With new 13.75-inch center drive wheels, a 3" ground clearance and new top speed of 4.4 mph / 7 km/h, it's built for crossing the threshold for indoor and outdoor use.

At just 22 inches, Jazzy EVO 614's turning radius comes in under two feet, which means your power wheelchair more easily navigates tight turns indoors and in your favorite shops and restaurants.

- 3" ground clearance
- 13.75" perforated mid-wheel drive tires
- Front and rear independent Active-Trac® ATX Suspension
- Removable matte-finish color-through shrouds
- Depth-adjustable, limited recline, memory foam heavy duty single seat post allows the user to swivel
- Access to controller and batteries without the user needing to exit the chair
- 60" lap belt

Available Colors



Accessories

- Cane/crutch holder
- Cell phone holder
- Cup holder
- Flag kit
- Oxygen tank holder
- Rear basket
- Saddlebag
- Stealth® cushions
- Walker holder
- Weather cover
- 2.1A XLR USB charger
- 50/70/80/90" lap belts

Options

- Swing-away joystick
- Elevated leg rests
- Swing-away leg rests
- Unoccupied transit
- Heel loops
- Residual limb support
- Solid seat pan, limited recline, high-back with swivel

Height, width, depth and angle adjustable armrests

Optional swing-away joystick

Depth-adjustable, limited recline, memory foam high-back seat with swivel

Removable color-through shrouds

Heavy duty seat post

Access to controller and batteries without the user needing to exit the chair

13.75" perforated drive wheels

Front and rear independent Active-Trac® ATX Suspension

FDA Class II Medical Device¹

Front and rear independent Active-Trac® ATX Suspension

Large footplate with removable rubber cover for easy cleaning

High-back memory foam seat

Scan QR code for more info.

