

www.ChallengerMobility.com

#### **ASSEMBLY INSTRUCTIONS**




#### **PARTS INCLUDED**

a-T Shaped Bracket



b - J900 Basket



c - 4 Phillips d - 2 Brackets



f- Locking knob

**TOOLS REQUIRED:** Phillips Screwdriver

## **ASSEMBLY INSTRUCTIONS**

- **1.** Place T shaped bracket (a) on work surface with screw holes facing up. Place basket (b) on top of T shaped bracket (a), parallel to cross bars
- 2. with T brace close to edge of basket (a).
- **3.** Align holes in 2 brackets (d) with holes in T shaped bracket (a), inside basket (b). Figure 1
- **4.** Pre start 4 screws (c) through 2 brackets (d), through the bottom of the basket (b), into the T shaped bracket (a). Run 4 screws (d) almost all

the way down. A thread lock compound may be applied to the 4 screws (c) to prevent them from loosening. But is not necessary.

### **MOUNTING INSTRUCTIONS**

- 1. Insert the end of the T bracket (a) into the accessory port on the back of the mobility scooter.
- **2.** Align the holes on the side of the accessory port with the holes in the T bracket (a).
- **3.** Insert clevis pin (e) in the side of the accessory port. Insert until clevis pin (e) protrudes from opposite side.
- **4.** Insert locking knob (f) into threaded port on top of accessory port. Tighten down to lock basket in place (applies only on specific models).



# CHALLENGER MOBILITY



# **MOBILITY ACCESSORIES AND MORE**